



### DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
125	90	600	140	139.4	139.7	140.8	141.1	125	125	849
125	45	600	140	139.4	139.7	140.8	141.1	125	125	459
125	30	600	140	139.4	139.7	140.8	141.1	125	125	311
125	22.5	600	140	139.4	139.7	140.8	141.1	125	125	234
125	15	600	140	139.4	139.7	140.8	141.1	125	125	157
125	11.25	600	140	139.4	139.7	140.8	141.1	125	125	118
125	90	1200	140	139.4	139.7	140.8	141.1	125	125	1697
125	45	1200	140	139.4	139.7	140.8	141.1	125	125	918
125	30	1200	140	139.4	139.7	140.8	141.1	125	125	621
125	22.5	1200	140	139.4	139.7	140.8	141.1	125	125	468
125	15	1200	140	139.4	139.7	140.8	141.1	125	125	313
125	11.25	1200	140	139.4	139.7	140.8	141.1	125	125	235
125	90	1830	140	139.4	139.7	140.8	141.1	125	125	2588
125	45	1830	140	139.4	139.7	140.8	141.1	125	125	1401
125	30	1830	140	139.4	139.7	140.8	141.1	125	125	947
125	22.5	1830	140	139.4	139.7	140.8	141.1	125	125	714
125	15	1830	140	139.4	139.7	140.8	141.1	125	125	478
125	11.25	1830	140	139.4	139.7	140.8	141.1	125	125	359

#### Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



**BEST ENVIRONMENTAL PRACTICE**



#### Contact

4 Aldinga Street, Brendale, Qld 4500  
 P.O Box 5066, Brendale QLD, 4500  
 ABN: 42 606 838 206  
 Ph: 1300 327 306

COMPLIES WITH AS/NZS 61386

1/05/2024