



DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
200	90	1200	225	224.3	224.7	225.9	226.3	200	200	1697
200	45	1200	225	224.3	224.7	225.9	226.3	200	200	918
200	30	1200	225	224.3	224.7	225.9	226.3	200	200	621
200	22.5	1200	225	224.3	224.7	225.9	226.3	200	200	468
200	15	1200	225	224.3	224.7	225.9	226.3	200	200	313
200	11.25	1200	225	224.3	224.7	225.9	226.3	200	200	235
200	90	1500	225	224.3	224.7	225.9	226.3	200	200	2121
200	45	1500	225	224.3	224.7	225.9	226.3	200	200	1148
200	30	1500	225	224.3	224.7	225.9	226.3	200	200	776
200	22.5	1500	225	224.3	224.7	225.9	226.3	200	200	585
200	15	1500	225	224.3	224.7	225.9	226.3	200	200	392
200	11.25	1500	225	224.3	224.7	225.9	226.3	200	200	294
200	90	1830	225	224.3	224.7	225.9	226.3	200	200	2588
200	45	1830	225	224.3	224.7	225.9	226.3	200	200	1401
200	30	1830	225	224.3	224.7	225.9	226.3	200	200	947
200	22.5	1830	225	224.3	224.7	225.9	226.3	200	200	714
200	15	1830	225	224.3	224.7	225.9	226.3	200	200	478
200	11.25	1830	225	224.3	224.7	225.9	226.3	200	200	359

Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



BEST ENVIRONMENTAL PRACTICE



Contact

4 Aldinga Street, Brendale, Qld 4500
 P.O Box 5066, Brendale QLD, 4500
 ABN: 42 606 838 206
 Ph: 1300 327 306

COMPLIES WITH AS/NZS 61386

1/05/2024