



## DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
20	90	150	20	19.4	19.7	20.1	20.4	20	20	212
20	45	150	20	19.4	19.7	20.1	20.4	20	20	115
20	30	150	20	19.4	19.7	20.1	20.4	20	20	78
20	22.5	150	20	19.4	19.7	20.1	20.4	20	20	59
20	15	150	20	19.4	19.7	20.1	20.4	20	20	39
20	11.25	150	20	19.4	19.7	20.1	20.4	20	20	29
20	90	300	20	19.4	19.7	20.1	20.4	20	20	424
20	45	300	20	19.4	19.7	20.1	20.4	20	20	230
20	30	300	20	19.4	19.7	20.1	20.4	20	20	155
20	22.5	300	20	19.4	19.7	20.1	20.4	20	20	117
20	15	300	20	19.4	19.7	20.1	20.4	20	20	78
20	11.25	300	20	19.4	19.7	20.1	20.4	20	20	59
20	90	450	20	19.4	19.7	20.1	20.4	20	20	636
20	45	450	20	19.4	19.7	20.1	20.4	20	20	344
20	30	450	20	19.4	19.7	20.1	20.4	20	20	233
20	22.5	450	20	19.4	19.7	20.1	20.4	20	20	176
20	15	450	20	19.4	19.7	20.1	20.4	20	20	117
20	11.25	450	20	19.4	19.7	20.1	20.4	20	20	88

### Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends