



DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
25	90	150	25	24.4	24.7	25.1	25.4	25	25	212
25	45	150	25	24.4	24.7	25.1	25.4	25	25	115
25	30	150	25	24.4	24.7	25.1	25.4	25	25	78
25	22.5	150	25	24.4	24.7	25.1	25.4	25	25	59
25	15	150	25	24.4	24.7	25.1	25.4	25	25	39
25	11.25	150	25	24.4	24.7	25.1	25.4	25	25	29
25	90	300	25	24.4	24.7	25.1	25.4	25	25	424
25	45	300	25	24.4	24.7	25.1	25.4	25	25	230
25	30	300	25	24.4	24.7	25.1	25.4	25	25	155
25	22.5	300	25	24.4	24.7	25.1	25.4	25	25	117
25	15	300	25	24.4	24.7	25.1	25.4	25	25	78
25	11.25	300	25	24.4	24.7	25.1	25.4	25	25	59
25	90	450	25	24.4	24.7	25.1	25.4	25	25	636
25	45	450	25	24.4	24.7	25.1	25.4	25	25	344
25	30	450	25	24.4	24.7	25.1	25.4	25	25	233
25	22.5	450	25	24.4	24.7	25.1	25.4	25	25	176
25	15	450	25	24.4	24.7	25.1	25.4	25	25	117
25	11.25	450	25	24.4	24.7	25.1	25.4	25	25	88

Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



BEST ENVIRONMENTAL PRACTICE



con-x
CONDUIT BENDS & FITTINGS

Contact

4 Aldinga Street, Brendale, Qld 4500
P.O Box 5066, Brendale QLD, 4500
ABN: 42 606 838 206
Ph: 1300 327 306

COMPLIES WITH AS/NZS 61386

1/05/2024