



## DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
32	90	150	32	31.4	31.7	32.1	32.4	32	32	212
32	45	150	32	31.4	31.7	32.1	32.4	32	32	115
32	30	150	32	31.4	31.7	32.1	32.4	32	32	78
32	22.5	150	32	31.4	31.7	32.1	32.4	32	32	59
32	15	150	32	31.4	31.7	32.1	32.4	32	32	39
32	11.25	150	32	31.4	31.7	32.1	32.4	32	32	29
32	90	300	32	31.4	31.7	32.1	32.4	32	32	424
32	45	300	32	31.4	31.7	32.1	32.4	32	32	230
32	30	300	32	31.4	31.7	32.1	32.4	32	32	155
32	22.5	300	32	31.4	31.7	32.1	32.4	32	32	117
32	15	300	32	31.4	31.7	32.1	32.4	32	32	78
32	11.25	300	32	31.4	31.7	32.1	32.4	32	32	59
32	90	450	32	31.4	31.7	32.1	32.4	32	32	636
32	45	450	32	31.4	31.7	32.1	32.4	32	32	344
32	30	450	32	31.4	31.7	32.1	32.4	32	32	233
32	22.5	450	32	31.4	31.7	32.1	32.4	32	32	176
32	15	450	32	31.4	31.7	32.1	32.4	32	32	117
32	11.25	450	32	31.4	31.7	32.1	32.4	32	32	88

### Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



**BEST ENVIRONMENTAL PRACTICE**



**con-x**  
CONDUIT BENDS & FITTINGS

#### Contact

4 Aldinga Street, Brendale, Qld 4500  
P.O Box 5066, Brendale QLD, 4500  
ABN: 42 606 838 206  
Ph: 1300 327 306

COMPLIES WITH AS/NZS 61386

1/05/2024