



DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
40	90	300	40	39.4	39.7	40.1	40.4	40	40	424
40	45	300	40	39.4	39.7	40.1	40.4	40	40	230
40	30	300	40	39.4	39.7	40.1	40.4	40	40	155
40	22.5	300	40	39.4	39.7	40.1	40.4	40	40	117
40	15	300	40	39.4	39.7	40.1	40.4	40	40	78
40	11.25	300	40	39.4	39.7	40.1	40.4	40	40	59
40	90	450	40	39.4	39.7	40.1	40.4	40	40	636
40	45	450	40	39.4	39.7	40.1	40.4	40	40	344
40	30	450	40	39.4	39.7	40.1	40.4	40	40	233
40	22.5	450	40	39.4	39.7	40.1	40.4	40	40	176
40	15	450	40	39.4	39.7	40.1	40.4	40	40	117
40	11.25	450	40	39.4	39.7	40.1	40.4	40	40	88
40	90	600	40	39.4	39.7	40.1	40.4	40	40	849
40	45	600	40	39.4	39.7	40.1	40.4	40	40	459
40	30	600	40	39.4	39.7	40.1	40.4	40	40	311
40	22.5	600	40	39.4	39.7	40.1	40.4	40	40	234
40	15	600	40	39.4	39.7	40.1	40.4	40	40	157
40	11.25	600	40	39.4	39.7	40.1	40.4	40	40	118

Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



Contact	COMPLIES WITH AS/NZS 61386	
4 Aldinga Street, Brendale, Qld 4500 P.O Box 5066, Brendale QLD, 4500 ABN: 42 606 838 206 Ph: 1300 327 306		1/05/2024