



DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
50	90	300	50	49.4	49.7	50.1	50.4	50	50	424
50	45	300	50	49.4	49.7	50.1	50.4	50	50	230
50	30	300	50	49.4	49.7	50.1	50.4	50	50	155
50	22.5	300	50	49.4	49.7	50.1	50.4	50	50	117
50	15	300	50	49.4	49.7	50.1	50.4	50	50	78
50	11.25	300	50	49.4	49.7	50.1	50.4	50	50	59
50	90	450	50	49.4	49.7	50.1	50.4	50	50	636
50	45	450	50	49.4	49.7	50.1	50.4	50	50	344
50	30	450	50	49.4	49.7	50.1	50.4	50	50	233
50	22.5	450	50	49.4	49.7	50.1	50.4	50	50	176
50	15	450	50	49.4	49.7	50.1	50.4	50	50	117
50	11.25	450	50	49.4	49.7	50.1	50.4	50	50	88
50	90	600	50	49.4	49.7	50.1	50.4	50	50	849
50	45	600	50	49.4	49.7	50.1	50.4	50	50	459
50	30	600	50	49.4	49.7	50.1	50.4	50	50	311
50	22.5	600	50	49.4	49.7	50.1	50.4	50	50	234
50	15	600	50	49.4	49.7	50.1	50.4	50	50	157
50	11.25	600	50	49.4	49.7	50.1	50.4	50	50	118

Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



Contact	COMPLIES WITH AS/NZS 61386	
4 Aldinga Street, Brendale, Qld 4500 P.O Box 5066, Brendale QLD, 4500 ABN: 42 606 838 206 Ph: 1300 327 306		1/05/2024