



DIMENSION TABLE

HD

DN	L1	L2	L3	D1	D2	WALL THICKNESS
25	25	12.5	62.5	25.1	30.7	2.8
32	32	16	80	32.7	38.7	3
40	40	20	100	40.1	46.9	3.4
50	50	25	125	50.1	57.9	3.9
63	63	31.5	157.5	63.1	72.1	4.5
80	80	40	200	89.2	99.8	5.3
100	100	50	250	114.8	128.2	6.7
125	125	62.5	312.5	140.8	157	8.1
150	150	75	375	160.8	179.4	9.3
200	160	80	400	225.9	249.3	11.7

COM

DN	L1	L2	L3	D1	D2	WALL THICKNESS
25	25	12.5	62.5	25.1	30.7	2.8
32	32	16	80	32.7	38.7	3
50	50	25	125	50.1	57.9	3.9
80	80	40	200	89.2	99.8	5.3
100	100	50	250	114.8	128.2	6.7

TEL / NBN

DN	L1	L2	L3	D1	D2	WALL THICKNESS
20	25	12.5	62.5	27	32.6	2.8
50	50	25	125	60.6	67.8	3.6
100	100	50	250	114.8	128.2	6.7

Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- Only Con-X standard Slip Couplings are listed
- Custom lengths are available and will be POA



BEST ENVIRONMENTAL PRACTICE



con-x
CONDUIT BENDS & FITTINGS

Contact

4 Aldinga Street, Brendale, Qld 4500
P.O Box 5066, Brendale QLD, 4500
ABN: 42 606 838 206
Ph: 07 3200 4100

COMPLIES WITH AS/NZS 61386

1/06/2024