



DIMENSION TABLE

DN	A (NOM)	R (NOM)	OD (NOM)	Dr Min	Dr Max	Dm Min	Dm Max	SC	SP	Length (L)
150	90	600	160.5	160.8	161.1	159.4	159.7	150	150	849
150	45	600	160.5	160.8	161.1	159.4	159.7	150	150	459
150	30	600	160.5	160.8	161.1	159.4	159.7	150	150	311
150	22.5	600	160.5	160.8	161.1	159.4	159.7	150	150	234
150	15	600	160.5	160.8	161.1	159.4	159.7	150	150	157
150	11.25	600	160.5	160.8	161.1	159.4	159.7	150	150	118
150	90	1200	160.5	160.8	161.1	159.4	159.7	150	150	1697
150	45	1200	160.5	160.8	161.1	159.4	159.7	150	150	918
150	30	1200	160.5	160.8	161.1	159.4	159.7	150	150	621
150	22.5	1200	160.5	160.8	161.1	159.4	159.7	150	150	468
150	15	1200	160.5	160.8	161.1	159.4	159.7	150	150	313
150	11.25	1200	160.5	160.8	161.1	159.4	159.7	150	150	235
150	90	1830	160.5	160.8	161.1	159.4	159.7	150	150	2588
150	45	1830	160.5	160.8	161.1	159.4	159.7	150	150	1401
150	30	1830	160.5	160.8	161.1	159.4	159.7	150	150	947
150	22.5	1830	160.5	160.8	161.1	159.4	159.7	150	150	714
150	15	1830	160.5	160.8	161.1	159.4	159.7	150	150	478
150	11.25	1830	160.5	160.8	161.1	159.4	159.7	150	150	359

Note

- All drawings, dimension, weights and volume are approximate only if critical please contact us
- Nominal size refers to the outside diameter 20-63 whereas greater than 80 refers to internal dimensions
- Sizes in red indicate multi-part bend
- Telstra and NBN conduit and fittings dimensions refer to AS/NZS 1477:2017 PVC pipes and fittings for pressure applications
- SP refers to spigot end
- M&F bends generally used in 1 direction sweep bends or multi part bends



BEST ENVIRONMENTAL PRACTICE



Contact

4 Aldinga Street, Brendale, Qld 4500
 P.O Box 5066, Brendale QLD, 4500
 ABN: 42 606 838 206
 Ph: 1300 327 306

COMPLIES WITH AS/NZS 61386

1/05/2024